

# GO X-TRA

The all-new ISUZU **X-RIDER**



ALL-NEW ISUZU  
IT'S A **D-MAX** THING  
Take it to its limits

SPECIFICATIONS:  
ISUZU 1.9 Ddi X-RIDER 4x4 A/T

[www.isuzu.co.za](http://www.isuzu.co.za) f X @ in

**ISUZU**



# ISUZU 1.9 X-RIDER 4x4 A/T

ENGINE	
Engine code	RZ4E-MID
Displacement (cc)	1898
No. of cylinders	4
Compression ratio	16.5:1
Bore x stroke (mm)	80 x 94.4
No. of valves	16
Power (kW) @ r/min	110 @ 3600
Torque (Nm) @ r/min	350 @ 1800-2600
Turbocharger	Standard
800 mm water depth protection	Standard
Pre-air cleaner	Standard
ACG (90A)	Standard
ACG with IBS (Intelligent Battery System)	Standard
Intercooler	Standard

FUEL CONSUMPTION <sup>1</sup>	
Combined Cycle (Litres/100 km)	7.6
Combined CO <sub>2</sub> Emissions (g/km)	199
Fuel Type	Diesel

TRANSMISSION	
Transmission Type	6 Speed Automatic
Gear Ratio: 1st	3.600
Gear Ratio: 2nd	2.090
Gear Ratio: 3rd	1.488
Gear Ratio: 4th	1.000
Gear Ratio: 5th	0.687
Gear Ratio: 6th	0.580
Gear Ratio: Reverse	3.732
4WD Selector	Standard
Low Range Ratio	2.482

FRONT DIFFERENTIAL	
Shift on the Fly up to 100 km / hour	Standard
Axle Ratio: Final Drive	4.1

REAR DIFFERENTIAL	
Differential Lock	Standard
Axle Ratio: Final Drive	4.1

CHASSIS DESIGN	
Front Wheel Suspension	High Mounting
Rear Wheel Suspension	Leaf Spring Overslung
Shock Absorbers	Twintube Gas Pressurised
Suspension	High Ride
Skid Plate Guard Front	Standard
Skid Plate Guard Rear	Standard
Engine Sump Guard	Standard
Transfer Case Guard	Standard
Oil Pan Guard	Standard

WHEELS AND TYRES	
Tyre Size	265/60R18 AT
Wheels Size / Type	Alloy 18" x 7.5J-33, Diamond Cut
Spare Wheel Size / Type	Alloy 18" x 7.5J-33, Diamond Cut
Turning Circle (m)	12.5
Tyre-Pressure Monitoring Sensor	-

DIMENSIONS	
Length (mm)	5265
Width (mm)	1870
Height (mm)	1805
Wheelbase (mm)	3125
Front / Rear Track (mm)	1570 / 1570
Rear Overhang (mm)	1250
Ground Clearance (mm)	227
Loadbox Length (mm)	1495
Loadbox Width (mm)	1530
Loadbox Depth (mm)	490
Approach Angle (°)	30.0
Departure Angle (°)	24.0
Breakover Angle (°)	22.5
Wading Depth (mm)	800

MASS / CAPACITY	
Gross Axle Mass - Front (GA1) (kg)	1450
Gross Axle Mass - Rear (GA2) (kg)	1910
Gross Vehicle Mass (GVM) (kg)	3100
Gross Combined Mass (GCM) (kg)	5000
Tare Mass (kg)	1935
Payload (kg)	1105
Towing Capacity (kg): Unbraked Trailer <sup>2</sup>	750
Towing Capacity / Rating (kg): Braked Trailer <sup>2</sup>	2100
Fuel Tank Capacity (Litres)	76

LOADBOX FEATURES	
Tiedown Brackets in Loadbox for Load Restraint	4
Rope Hooks on Loadbox Side	-

SAFETY FEATURES	
Anti-Lock Braking System (ABS)	Standard

Electronic Brake Force Distribution (EBD)	Standard
Brake Assist System (BAS)	Standard
Electronic Stability Control (ESC) with Traction Control	Standard
Hill Start Assist (HSA)	Standard
Hill Descent Control (HDC)	Standard
Trailer Sway Control	Standard
Brake Override Accelerator (BOA)	Standard
Cruise control	Standard
Multi collision brake	-
Height adjustable 3-point front seat belts	Standard
Front seat centre lap belt (2 point)	-
Seat belt pretensioners	Standard
Fixed 3-point rear seat belts	Standard
Seat belt reminder	Driver & Passenger
Occupant detection sensor	Passenger
Driver & Passenger airbags	Standard
Front seat side airbags	Standard
Curtain airbags	Standard
Knee airbag	Driver
Far side airbag	-
Side impact protection bars	Standard
Improve side pole impact	-
Collapsible steering column	Standard
Speed sensitive door lock	Standard
ISOFIX child seat attachment	Standard with Top Tether
Parking distance sensors	Rear
Rear view camera	Standard
Front camera	-
Warning triangle kit	Standard
Emergency stop signal	Standard
Blind spot monitor	-
Rear cross traffic alert	-
Rear radar	-
Autonomous emergency brake	-
Forward collision warning	-
Pedal misapplication mitigation	-
Manual speed limiter	-
Lane departure warning	-
Lane keep assist	-
Lane departure prevention	-
Driver monitoring	-

SECURITY FEATURES	
Manual Door Locks	-
Remote-Controlled Central Locking	Standard
Remote Keyless Entry	Standard
Remote Engine Start	-
Passive Entry Start System (PRESS)	-
Child-Proof Rear Door Locks	Standard
Anti-Theft Alarm System	Standard
Ultrasonic Alarm	Standard
Transponder Immobiliser System	Standard
Selectable Door Unlock	Standard
Walk-Away Auto Door Lock	-

INTERIOR / EXTERIOR LIGHTING	
Front Reading Lamps	Standard
Interior Courtesy Lamps	Standard
Illuminated Entry	Standard
Front Fog Lamps	Standard, LED
Daytime Running Lights (DRL)	LED
Headlamps	LED
Headlamp Levelling	Manual
Headlamps 'ON' Warning Buzzer	Standard
Automatic On/Off Headlamp	-
Automatic High Beam	-
Turn Indicator Lamp on Door	-
Rear Taillights - Combination	LED
High-Mounted Centre Stop Lamp	LED
Rear Fog Lamps	-
Follow-Me-Home Headlamps	Standard

EXTERIOR FEATURES	
Front Wiper	Variable Intermittent
Radiator Grille	Gloss Black, Red Badge
Front Bumper	Body Colour
Rear Bumper	Body Colour
Front Bumper Cladding	-
Towbar	Standard (2.1T)
Exterior Door Handle	Black
Exterior Mirror	Black, Power Adjustment and Manual Folding, Side Indicator
B-Pillar Blackout	Standard
Over Fender (Fender Flares)	-
Roof Rails	Standard
Sports Bar	Standard
Sports Hoop	-
Side-Steps	Standard, Black
Mudflaps	Front & Rear
Tailgate Handle	Body Colour

Cab Protector	-
INTERIOR FEATURES	
Power-Assisted Steering (PAS)	Hydraulic
Air Conditioning	Manual
Pollen Filter	Standard
Inside Rear-View Mirror	Day / Night
Sunvisor	Driver with Ticket Holder, Passenger with Vanity Mirror
Overhead Console with Map Lamps (X2) and Sunglasses Holder	Standard
Digital Clock	Standard
Cruise Control	Standard
Multi-Information Display (MID)	Standard with X Mark
Dashboard Illumination Control	Standard
Power Socket - Auxiliary 12V IP Mounted	1
Cigarette Lighter	Standard
Lockable Glove Box	Standard
Utility Box on Glove Box	Standard, High Type, X Mark with Red Gradation
Steering Column Adjustment	Tilt & Telescopic
Steering Wheel Trim	Leather with Red ISUZU Badge/Stitching
Steering Wheel Multi-Functional Controls	Audio & Auto Cruise
Gear Shift Trim	Urethane, Red Stitch Knob and Boot
Front Seat Configuration	2 x Bucket
Rear Seat Configuration	Bench, Split Cushion 60:40
Seat Trim	Partial Leather X Mark on Headrest with Red Stitching
Seat Adjustment	6 Way Manual Driver
Storage Pockets behind Front Seats	Standard
Door Trim with Storage Pockets and Integrated Cupholders	Standard
Interior Door Release Handle	Black
Interior Trim Colours	Black Upper / Black Lower
A-pillar Assist Grip - Driver and Passenger	Standard
Roof-Mounted Assist Grips	Driver & Passengers
Floor Trim	Carpet with Heel Pad & Tibia Pad, X-Rider Floor Mats
Floor Tunnel Console with Integrated Cupholder	Standard
Centre Console Storage Box with Lid	Standard
Driver Footrest	Standard
Rear Heater Duct	Standard
Rear Ventilation Duct	-
Storage Box	-
Window Operation	Power Front & Rear with Driver One Touch, Jam Protection
Rear Window	Fixed without Defogger
Fuel Flap Remote Opener	Standard
Ventilator Grille with Shutter (Fin Shut)	Standard

INFOTAINMENT	
Audio System	AM/FM Radio, 7" Touch Screen, Bluetooth - Audio Streaming, Apple CarPlay & Android Auto, WiFi & Handsfree Phone
USB Port (Music Playback and Device Link)	Standard
USB Charge Port	Rear
Speakers	6
Antenna	Standard

OPTIONS	
17" Alloy Wheel	-
18" Alloy Wheel and 265 / 60 R 18 Tyre (All Terrain)	-
18" Alloy Wheel and 265 / 60 R 18 Tyre (H/T Terrain)	Available
Differential Lock	-
Hubcap Steel Wheel	-
Hubcap Alloy Wheel	-
Spare Tyre Steel	-
Spare Tyre Alloy	-
Sports Bar - Black	-
Sports Bar - Chrome	-
Rear Sliding Window	Available
Partial Leather Seat with Manual Adjustment	-
Body Colour Front Bumper	-
Body Colour Rear Bumper	-
Safari beige	-
Safari beige with black rear step	-

WARRANTY / SERVICE INTERVALS	
Warranty and Roadside Assistance	5 years / 120 000 km
Anti-Corrosion Warranty	5 years / unlimited km
Service Plan	5 years / 90 000 km
Service Intervals	12 months / 15 000 km

1 Fuel Economy and CO<sub>2</sub> data as per ECE R101 / SANS 20101 regulation. Note that the actual fuel consumption will depend on many factors including the driver's driving habits, prevailing conditions and the vehicle's equipment, condition and use.

2 Towing capacity subject to South African Road Traffic Act. The weight of the towing vehicle including trailer towball load must not exceed the Gross Vehicle Mass (GVM). The combined weight of the fully loaded vehicle and trailer must not exceed the Gross Combination Mass (GCM). Maximum individual axle loads (GA1 and GA2) must not be exceeded. (e.g. if a 3.0L Diesel is towing 3.500kg its maximum Vehicle mass is 2.500kg in order to be within GCM).